



The state of the second second second second second

OTTE FILE COPY

OFFICE OF NAVAL RESEARCH
Contract N00014-87-K-0517
R&T Code 4132001---02

TECHNICAL REPORT NO. 4

Blends of Crystallizable Polybutadienes

bу



M. Marx and R. E. Cohen

Department of Chemical Engineering

Massachusetts Institute of Technology

Cambridge, Massachusetts 02139

April 25, 1988

Reproduction in whole or in part is permitted for any purpose of the U.S. government.

This document has been approved for public release and sale; its distribution is unlimited.

SECURITY CLASSIFICATION OF THIS PAGE								
	REPORT DOCUM	MENTATION	PAGE					
1a. REPORT SECURITY CLASSIFICATION		16. RESTRICTIVE	MARKINGS					
2a. SECURITY CLASSIFICATION AUTHORITY		,	AVAILABILITY O					
2b. DECLASSIFICATION / DOWNGRADING SCHEDU	LE		for public ion is unli					
4. PERFORMING ORGANIZATION REPORT NUMBE	R(S)	5. MONITORING	ORGANIZATION R	EPORT NUMBER	S)			
Technical Report No. 4	·	•			·			
6a. NAME OF PERFORMING ORGANIZATION	66. OFFICE SYMBOL	7a. NAME OF MO	ONITORING ORGA	NIZATION	·			
MIT Dept. Chem. Eng.	(If applicable)	ONR		٠.	·			
6c. ADDRESS (City, State, and ZIP Code)	·	76. ADDRESS (Cir	y, State, and ZIP	Code)				
Cambridge, MA 02139			Quincy St. on, VA 2221	.7				
84. NAME OF FUNDING / SPONSORING	86. OFFICE SYMBOL	9. PROCUREMENT	INSTRUMENT ID	ENTIFICATION N	JM8ER			
ORGANIZATION Office of Naval Research	(If applicable)	N00014-87-	-K-0517					
Bc. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF F	UNDING NUMBER	RS				
	!	PROGRAM	PROJECT	TASK	WORK UNIT			
		ELEMENT NO.	NO. 4132001	NO02	ACCESSION NO.			
12. PERSONAL AUTHOR(S) M. Marx and R.E. Cohen	M. Marx and R.E. Cohen Cohen Marx and R.E. Cohen Marx and R							
19. ABSTRACT (Continue on reverse if necessary	and identify by block n	umber)			<u>`</u>			
This report provides base (trans 1,4 PBD and syndiotace Blends were prepared, by a solution and molecular characterization and syndiotace and syndiotace and syndiotace are supplied to the syndiotace are suppli	seline data on to tic 1,2 PBD) and Lution casting m	wo crystalli on 50/50 we ethod discus	ight percen sed in the	t homopolym report. Re	er blends. /			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT		1	CURITY CLASSIFIC	ATION				
■ UNCLASSIFIED/UNLIMITED □ SAME AS	RPT. 🗀 DTIC USERS	Unclassi						
223. NAME OF RESPONSIBLE INDIVIDUAL		1226. TELEPHONE	include Area Code	e) 22C OFFICE S	YMBOL			
OD 50 PM 1473 PA MAR 83 A	PR edition may be used un	I evnausted						

All other editions are obsolete.

Blends of Crystallizable Polybutadienes

M.Marx and R.E. Cohen

Department of Chemical Engineering

Massachusetts Institute of Technology

Cambridge, MA 01239

Abstract

This report provides baseline data on two crystallizable polybutadiene homopolymers (trans 1,4 PBD and syndiotactic 1,2 PBD) and on 50/50 weight percent homopolymer blends. Blends were prepared by a solution casting method discussed in the report. Results of molecular characterization and thermal analysis experiments are presented.



Accesio	on For	1
DTIC	ounced	
By Distrib	site of	
Λ	validhility	Codes
Dist	Avail and apeck	
A-1		

INTRODUCTION

The second secon

This progress report describes work done to date on the topic "Blends of Crystallizable Polybutadienes: Morphology Control via Diblock Addition in the Melt". The objectives of the research are to determine: a) the compatibility and behavior of binary blends of crystallizable syndiotactic 1,2 and trans 1,4 polybutadienes (PBD), and b) the effect of amorphous 1,2/1,4 PBD diblocks on the crystallization and phase separation of these blends. Work to date has focused on characterization of the individual homopolymers and of 50/50 (wt%/wt%) blends of the homopolymers. We have obtained IR, NMR, and DSC data for the homopolymers. Conditions for spincast solution blending of these materials were optimized and the resultant blends were analyzed using DSC.

HOMOPOLYMERS

The polybutadiene homopolymer samples were obtained in powder form from Dr. A.F. Halasa of Goodyear Tire and Rubber Company in Akron, OH. Both syndio 1,2 and trans 1,4 PBD have a molecular weight of 54.09 grams per repeat unit.

The syndiotactic PBD was made on or before 10/29/85, and was reported by Halasa to have a melting point of 195 C and to have a structure of 90% 1,2 units and 10% 1,4 units as determined by IR. Syndio PBD crystals are orthorhombic and have unit cell dimensions of a=10.98A, b=6.60A, and c=5.14A (Natta and Corradini, 1956). Heat of fusion of pure syndio is at least 24.6 cal/g (Ashitaka, 1983a).

The trans polymer was made by Zeigler-type catalysis, and was reported by Halasa to have a melting point of 150 C and a structure that is about 90% trans. Trans PBD is polymorphic, having one crystal form below about 75 C that is referred to as modification I (mod I) and a second form between 75 C and the melting point, referred to as modification II (mod II). According to Iwayanagi et al. (1968), mod I crystals are monoclinic with crystal dimensions of a=8.63A, b=9.11A, and c=4.83A. According to Natta and Corradini (1959), mod I crystals are pseudohexagonal with lattice dimensions a=4.54A and c=4.92A and according to Seuhiro et al. (1970), a=4.60A and c=4.83A. The transition to mod II is reversible and is characterized by a 9% increase in volume (Natta and Corradini, 1959). Mod II crystals are psuedohexagonal and have dimensions a=4.88A, c=4.68A (Natta and Corradini, 1959) or a=4.95A, c=4.66A (Seuhiro et al., 1970). There is also some disagreement in the literature as to the exact temperatures and enthalpies

associated with the various transitions, as shown in Table 1. To calculate trans PBD crystallinity fractions in our samples, we used Danusso's (1966) values of 40.6 cal/g for the enthalpy of transition between mods I and II and 20.3 cal/g for the enthalpy of melting.

BLENDING

Blending of polymers is generally accomplished in one of three ways: 1) mechanical blending of the melt followed by compression molding, 2) solution precipitation followed by compression molding and 3) solution casting directly into films. The last procedure is usually done by slow solvent evaporation onto a flat glass plate. In our lab, however, a spin casting method (Bates et al, 1983) is employed whereby the polymer solution is spun in an aluminum cup. As the solvent is driven off by a stream of nitrogen, a film forms on the cup wall. The wall is lined with Mylar so that the film can then be removed from the cup and peeled from the Mylar.

All but the first technique listed above require solvent for the polymers. Neither the trans nor the syndio PBD samples obtained from Goodyear were soluble in boiling toluene (110 C); syndio (but not trans) dissolves in boiling xylene (140 C). Ashitaka et al. (1983b) used o-dichlorobenzene (bp 177 C) and tetralin (1,2,3,4 tetrahydronapthalene, bp 207 C) as solvents for syndio PBD at 140 C. Our studies indicate that trans PBD goes into o-dichlorobenzene at about 130 C but separates from the solvent and into a gel-like blob as soon as the temperature drops, making the material difficult to handle. Both homopolymers go into solution well in tetralin: trans at 105 C and syndio at 125 C.

One percent to 1.5% solutions of the homopolymers in hot tetralin (160 C) were poured into a preheated spincasting cup (120 -150 C) and then processed at 160 C. Ethyl 330 antioxidant (1,3,5 trimethyl-2,4,6-tris[3,5-di-tert-butyl-4-hydroxybenzyl]benzene) was added to all solutions in concentrations up to 0.05g/g polymer. Nitrogen purged the cup at rate of 10 SCFH. After 16 hours, the temperature controller was turned off and the temperature decreased to about 40 C, usually after a period of about three hours, the film was removed from the cup and placed in a room temperature vacuum oven for a sufficient time to remove residual solvent. These conditions gave tan-colored trans PBD films and light yellow syndio PBD films. The as-received trans homopolymer powder is slightly off-white in color, thus the tan color of the trans films suggests that the films

oxidized. The syndio homopolymer powder is initially light yellow, so there may be only minor oxidation in these samples. Detailed further investigation into the role of antioxidant in preventing oxidative degradation of processed films is underway.

The syndio films separated from the Mylar during the spin casting process. The trans films, on the other hand, generally stuck to the Mylar and could not be peeled off without ruining the film. These observations suggest that the syndiotactic polymer crystallizes from solution during the casting process, whereas the trans polymer remains an amorphous melt during the casting process and crystallizes later during cooling in the bulk state. To prevent the trans from sticking, we lowered the processing temperature to 120 C, below the melting point of the trans. Keeping all other conditions the same, this change gave trans films which adhere to the Mylar, yet were removable if peeled off slowly and carefully.

Fifty/fifty blends of the two homopolymers cast at both 160 C and 120 C yielded films that stuck to the Mylar yet came off with the aid of a razor blade. The texture and color of these films were intermediate between those of the homopolymer films. Without the aid of microscopy, the morphologies of the blends appeared not to be uniform. Further details await the results of ongoing microscopic analysis.

GEL PERMEATION CHROMATOGRAPHY

For the purpose of characterizing the as-received samples, we have attempted to obtain high temperature gel permeation chromatography data on the two homopolymers. A Waters 150C GPC was used at 140 C with tetralin as the mobile phase. No antioxidant was added to the polymer solutions (0.1 to 0.8%).

Results showed that extensive degradation of the polymers occurred in the GPC, to the extent that all elution times were longer than that of the lowest molecular weight polystyrene standard (M=2,400 g/mole).

Successful protection of the chains from degradation during the GPC experiments is a high priority for the forthcoming period of work so that the extent of molecular deterioration during sample processing can be documented and reduced if necessary.

INFRARED SPECTROSCOPY (IR)

IR was performed to examine the microstructure of the homopolymers. Small amounts of the homopolymer powders were placed between two slides and heated on a hot plate until the polymer melted. The slides were then removed from the heat. Enough polymer was used to ensure a thin film at least 1/2 inch in diameter. When the slides reached room temperature, they were carefully pried apart. The pressed polymers were removed from the slides with a razor blade and taped onto sample holders for the IR spectrometer (Perkin-Elmer, model 727B). To check reproducibility, spectra show were obtained for various positions of the samples. To determine an approximate range of error, each spectrum was run twice on the same sheet of paper.

Our results are in Figures 1b and 2b and are listed in the first column of Tables 2A and 2B for syndio and trans, respectively. Our data agree very well with spectra of Morero et al. (1960, 1962) shown in Figures 1a and 2a and listed in the second column of Tables 2A and 2B for syndio and trans. Other published polybutadiene spectra and data include only certain bands, as listed in the third columns of Tables 2A and 2B. Assignments are found in the Morero papers mentioned above. In the spectrum for syndio, we obtained bands between 2130 and 2330 cm⁻¹ that are not reported in the literature, and our trans spectra show a broad band at 2340 cm⁻¹ that is not documented in the literature. At present we have no explanation for these bands.

A spectrum for a spincast trans film, shown in Figure 2c, gave identifiably trans data; however, some peaks are more pronounced than in the melt-cast trans sample while others are less pronounced.

NUCLEAR MAGNETIC RESONANCE SPECTROSCOPY (NMR)

 1 H-NMR was performed on 1.5% syndio solutions and 1.0% trans solutions in 307. deuterated tetralin at 150 C and 250 Hz. Syndio samples (2.07%) and trans (1.5%) in tertralin at 150 C were used for the 13 C-NMR. In the absence of an internal standard, the spectra were referenced to the spectrum for tetralin.

In addition to the solvent peaks, we obtained ¹H-NMR peaks at 2.3, 5.1-5.5, and 7.7 ppm for syndio and 2.2, 5.6, and 7.7 ppm for trans, as shown in Figures 3b and 3c. Table 3 lists our data along with literature values and assignments for both 1,2 and 1,4 PBD. Values that are specifically for syndio 1,2 and trans 1,4 are designated as such in the table. Trans peaks appear farther downfield

than expected and two syndio peaks found in the literature around 1.3 and 5.5-5.6 ppm are not present in our spectra at all. Both PBD samples gave a peak at 7.7 ppm that is not reported in the literature for PBD or tetralin. * Samples with higher concentrations in perdeuterated tetralin will be examined in an attempt to obtain better data for both $^1\mathrm{H}$ and $^{13}\mathrm{C-NMR}$.

Solid state Magic Angle Spinning (MAS) 13C-NMR was performed on both homopolymers. The cross polarized, proton decoupled spectra are shown in Figure 4a for syndio PBD and in Figure 4b for trans PBD. Syndio peaks are at 40, 118, and 143 ppm. for the trans PBD, a doublet occurred at 33,35 ppm and at 130,131 The smaller peaks are sidebands of the latter doublet and appear due to limits in the spinning speed of the sample. These data are listed in Table 4 along with data of Schilling et al. (1984, 1987) and Moller (1984). We found no literature on solid state NMR for syndio PBD, but by analogy to solution 13-NMR, we expected four peaks around 39, 41-42, 114, and 143 ppm. We do not have an explanation for the appearance of three peaks in our data on the syndio polymer. The trans PBD doublet at 33,35 ppm can be assigned to aliphatic (methylene) carbons and the doublet at 130,131 to olephinic carbons. Schilling et al. temperature MAS 13 -C-NMR data for trans confirm this conclusion. They obtained the same doublets that we did and claim that doublets demonstrate resonances of the amorphous and crystalline carbons, with the amorphous carbons being slightly upfield from the crystalline carbons. Moller obtained MAS data at 27 C and also observed splitting of the methylene signal. Schilling et al. (1987) and Moller also report solid state data for trans at various temperatures above room temperature. Moller's spectra at 27, 52, 67, 122, and 134 C respectively correspond to the following states of trans: mod I, mod I, transition between mod I and mod II, mod II and melt. Note that there are a total of three methylene signals over the range of Moller's data. These signals represent the three trans states, i.e. mod I, mod II, and the amorphous melt, and are characterized by an upfield shift with increased amorphous content. Schilling et al. data at 23, 59, 62, and 65 C, temperatures which he claims represent mod I, the transition between mod I and mod II, the transition between mod I and mod II, and mod II. Moller suggests that the 65 data represents the transition between mod I and II while the other temperatures are various representations of mod I.

 $^{^{\}star}$ Our ^{13}C (solution) NMR data gave inconclusive results.

Our results are similar to the Schilling et al. (1984) room temperature data and to Moller's data at 52 C.

DIFFERENTIAL SCANNING CALORIMETRY (DSC)

DSC was employed to determine the crystallization behavior of the homopolymers and blends of the homopolymers. In particular, the following information was monitered: 1) the melting and transition points of the homopolymers and the associated enthalpies, 2) the effect of spincasting on the melting points and enthalpies, and 3) the effect of blending for the particular case of 50/50 homopolymer blends.

Tests were performed on a Perkin-Elmer DSC4 with a Thermal Analysis Microprocessor and a Thermal Analysis Data Station (TADS). Five to 15 mg of polymer were heated and cooled in aluminum pans at specified rates. Most samples were heated at a rate of 10 C or 20 C per minute to about 30 C beyond the melt temperature. At the end of a heating trial, the samples were usually quenched from the melt to room temperature at a nominal rate of 320 C/min.

RESULTS AND DISCUSSION

The second of th

All of the tests performed to date are listed in Table 5 along with data of prior history, heating rate, melting or other transition points, the enthalpies associated with these points, and the crystallinity fractions of the components in the samples. Crystallinity fractions were calculated using values of 24. 6 cal/g for 100% crystallized syndio (Ashitaka, 1983a), and 40.6 cal/g for the transition between modifications I and II of trans (Danusso, 1966). In this report, DSC trials will be referred to by the number assigned them on the left of this table.

The melting point for the syndio homopolymer samples, T(s), ranged from 164 C to 197 C and the crystallinity ranged from 37% to 79% where the higher percentages are for those samples tested as received from Goodyear and the lower values are generally from those that are spincast, remelted, and then quench-cooled at -320 /min. The transition between trans I and II, T(tI), of the homopolymer samples ranged from 71 to 80 C and the mod II melting point, T(tII), was 125 to 150 C. Trans homopolymer crystallinity based on the low temperature

transition was 40% to about 58%.

Bermudez and Fatou (1972) observed that the crystallinity of trans PBD decreased during the transition from mod I to mod II, indicating that there is not complete conversion from mod I to mod II. In our trials #15 and #16, the enthalpy of mod II increased when the temperature was held constant for ten minutes between T(tI) and T(tII), showing that the rest of our trials, which were not held isothermally between these two temperature, definitely do not undergo complete conversion. Therefore, we recognize that calculated trans crystallinity fractions based on mod I enthalpies may be somewhat lower than the true degree of trans crystallinity.

In all of the blends, the three transitions characteristic of our homopolymers were present, two transitions for trans and one for syndio. Thus our blends were not homogeneous below 200 C and did not show any significant signs of isomorphic or eutectic behavior.

In three trials (#30, #31), blends were heated above 400 C. Beyond 280 C, oxidation and/or crosslinking occurred followed by degradation. In these trials, an endothemic shift in the baseline occurred between about 230 -255 C. This has not yet been investigated in detail but we feel that it may indicate the presence of an upper critical solution temperature (UCST) for the blends. If so, this would provide opportunities for exploring crystallization from homogeneous melts (at T>Tucst) quenched to a selected crystallization temperature. This possibility will be explored in detail in the immediate future.

In order to compare data meaningfully, we needed to determine what did or did not constitute a significant difference in results. This determination of "significant difference" was accomplished by comparing conducted at identical conditions trials. The difference between values obtained for a given parameter from identical runs was insignificant, as shown clearly in Table 6. The maximum differences observed for trials with identical conditions were 1.2 C and 0.9 cal/g. A comparison between trials #30 and #31 demonstrates that the spincasting procedure gives reproducible blends. T(tI) and T(s) values differed by less than 2 C from sample to sample. The T(tII) values differed by 6 C and were both much lower than in all of the other trials listed in Table 6, perhaps due to the low casting temperature of these two samples. H(tI) and H(s) values were within 0.1 cal/g of each other for these two samples while H(tII) values were within 0.7 cal/g..

In trials #27 and #28, all of the values are low compared to the other samples cast at 160 C. These samples had had many tests performed on them before trials #27 and #28 were conducted, and they may have become crosslinked or otherwise altered in the process. Thus the results from these trials may be unreliable but they do point out the need for concern about repeated experiments at elevated temperatures for these materials.

Two interesting categories of experiments in Table 5 lend themselves to further comparisons. Category I includes trials for samples of a given composition in which the cooling and casting histories of the samples are different but the heating rates are the same as shown in Table 7A. Category II encompasses trials of spincast samples for which the sample compositions vary. All of the groups in Category II are listed in Table 7B.

Comparisons listed in Table 7A for Category I show the effects of prior crystallization rate and of casting. Regarding crystallization history, for two samples of the same composition that were cooled at different rates, the melting points(s) and enthalpies of the sample crystallized from the melt at -320/ were less than or equal to those of a sample crystallized at a slower rate.

Casting effects on the homopolymers can be determined by comparing trials in Category I. Cast homopolymers that were quenched from the melt at 320 /min always gave lower melting points than the same uncast homopolymers quenched from the melt. The enthalpies of the cast homopolymers were less than or equal to those of the uncast materials. This result may reflect the presence of residual solvent and/or some degradation in the cast materials, although it may also reflect real differences in crystallization from solvent-based processing of these polymers.

In group IE, we can compare the results of spincasting 50/50 blends at 160 C and 120 C. We suspect that with 160 C casting, syndio crystallizes from solution at some point during the casting process, as the solvent is driven off, whereas, trans at this temperature is in the melt state and thus remains uncrystallized throughout the casting process. When the apparatus is cooled to room temperature, the trans polymer then must crystallize in the presence of syndio crystals. When processed at 120 C, which is below both melting points, syndio and trans both can crystallize during the casting process and crystallization of each component might be impeded by the other. This was apparently observed. All melting point and enthalpy values were higher for the sample cast at the higher temperature, though T(tI) was relatively constant. The crystallinity fraction of the syndio

component dropped from 0.54 to 0.44 and the trans crystallinity dropped from 0.39 to 0.26 when cast at 120 C compared to 160 C.

From groups of trials in Category II (Table 7B) we see the effect of blending on the individual components in the blend. For a given component, the melting point in the blend was always lower than that of the pure homopolymer cast under identical conditions, except for syndio PBD in Case IIC. Additionally, the enthalpy of trans (per gram of trans in sample) was lower in the blends than in the homopolymer and the syndio enthalpy in the IIA blend is less than its homopolymer enthalpy. As discussed earlier, since these samples were cast at 160 C, we suspect that the syndio crystallized from solution while the trans remained in the melt state, then when the bulk sample was cooled from 160 C, the trans also crystallized but was impeded by the presence of the syndio crystals. In case IIA, the syndio crystallinity was lower in the blend than in the homopolymer by 17% and the trans was lower by 19%. In cases IIB and IIC, the syndio enthalpy per gram of syndio was approximately equal to the enthalpy per gram of pure syndio under the same conditions, suggesting that syndio crystallization was not at all impeded by the presence of the trans chains in solution. In these cases, the crystallization of the trans was 27-28% lower in the blend than in homopolymer. In case IIA, the sample was slowly cooled in the spin caster and in cases IIB and IIC the samples were cooled at 320 C/min from the melt.

SUMMARY OF DSC OBSERVATIONS

CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR

COCCUPATION OF STREET PROPERTY OF THE PROPERTY

Syndio homopolymer melting points ranged from 164 C to 197 C, depending on the sample history, and samples had crystallinities from 37% to 79%. The trans homopolymer mod I transition ranged from 71 C to 80 C and mod II transition from 125 C to 150 C. Crystallinity based primarily on mod I enthalpies ranged from 40% to 58%.

The homopolymers behaved in an explainable fashion with regard to cooling/heating behavior. In particular, for samples with identical prior histories, reheat rate did not affect enthalpy content at a transition point, yet the higher the heating rate, the higher the melting point. Upon reheating samples with different prior cooling histories from the melt, the samples that had been cooled more quickly had melting points and enthalpies less than or equal to the more slowly cooled samples.

The spincasting process generally resulted in lower melting point and

enthalpies than those observed for samples that had not been spincast.

In all of the blends, three transitions were present (two for trans, one for syndio). Components of the blends had lower melting points than homopolymer samples cast under the same conditions. The enthalpy of trans in the blends (per gram of trans) was ~20-30% less than in the corresponding trans homopolymer, suggesting that its crystallization was impeded by the presence of the syndio. In a slowly cooled blend, syndio crystallization was 17% less than that of the syndio homopolymer, but in quench-cooled blends, the enthalpy of the syndio was unaffected by the presence of the trans. Crystallinity fractions were lower in samples cast at 120 C, which is below both component melting points, than in samples cast at 160 C, which is below the melting point of syndio only.

ONGOING CHARACTERIZATION OF HOMOPOLYMERS AND BLENDS

Methanol precipitation of polymer solution followed by compression molding of the dried powder is being investigated as an alternative to spincasting. To further characterize the homopolymers and blends, wide angle X-ray scattering is being carried out. Homopolymer and blend films will also be subjected to Rheovibron testing at temperatures from -150 C to 250 C; the low-temperature data will tell us something about the nature of the amorphous regions of our samples. The postulated upper critical solution temperature (UCST), will be investigated in detail by gathering more DSC data around this point and by means of mechanical spectroscopy, light microscopy, and cloud point determinations.

References

Ashitaka, H., K. Inaishi, and H. Ueno, <u>Journal of Polymer Sciences: Polymer Chemistry Edition</u>, <u>21</u>, 1973, 1983a.

Ashitaka, H., H. Ishikawa, H. Ueno, and A. Nagasaka, <u>Journal of Polymer Science:</u>
Polymer Chemistry Edition, 21, 1853, 1983b.

Bates, F.S., R.E. Cohen, and A.S. Argon, Macromolecules, 16, 1108, 1983.

Bautz, G., U. Leute, W. Dollhopf, and P.C. Hagele, Colloid and Polymer Science, 259, 714, 1981.

Berger, M., and D.J. Buckley, Journal of Polyer Science: A1, 2945, 1963.

Bermudez, S.F., and J.M.G. Fatou, European Polymer Journal, 8, 575, 1972.

Binder, J.L., Journal of Polymer Sciences: A1, 47, 1963.

Chen, H.Y., Analytical Chemistry, 34, 1134, 1962.

Dainton, F.S., D.M. Evans, F.E. Hoare, and T.P. Melia, Polymer, 3, 297, 1962.

Danusso, F., Polymer, 8, 281, 1967.

Drzewinski, M.A., Polymer Materials Science and Engineering, 53, 113, 1985.

Finter, J., and G. Wegner, Makromolekukare Chemie, 182, 1859, 1981.

Foley, A., MIT Chemistry Department, Personal Communication, July, 1987.

del Giudice, L., R.E. Cohen, G. Attalla, and F. Bertinotti, <u>Journal of Applied Polymer Science</u>, 30, 4305, 1985.

Hampton, R.R., Analytical Chemistry, 21, 925, 1949.

The second second

Hatada, K., Y. Terawaki, H. Okuda, Y. Tanaka, and H. Sato, <u>Journal of Polymer</u> Science: <u>Polymer Letters Edition</u>, <u>12</u>, 305, 1974.

Hendrix, C., D.A. Whiting, and A.E. Woodward, Macromolecules, 4, 571, 1971.

Iwayanagi, S., I. Sakurai, T. Sakurai, and T. Seto, <u>Journal of Macromolecular Science - Physics</u>, <u>B2</u>, 163, 1968.

Kijima, T., M. Imamura, and N. Kusumoto, Polymer, 17, 249, 1976.

Mandelkern, L., M. Tryon, and F.A. Quinn, Jr., <u>Journal of Polymer Science</u>, <u>19</u>, 77, 1956.

Marchetti, A., and E. Martuscelli, <u>Journal of Polymer Science: Polymer Physics</u> Edition, 14, 151, 1976.

Moller, M., American Chemical Society (ACS) Polymer Preprints, 28, (2), 395, 1987.

Moraglio, G., G. Polizzotti, F. Danusso, European Polymer Journal, 1, 183, 1965.

Morero, D., F. Ciampelli, and E. Mantica, Advances in Molecular Spectroscopy, Proceedings of the Fourth International Meeting, 2, 898, ed. a. Mangini, Pergamon Press, England, 1962.

Morero, D., E. Mantica, and L. Porri, Nuovo Cimento, Suppl. 15, 10, 136, 1960.

Morero, D., A. Santambrogio, L. Porri, and F. Ciampelli, Chimica e Industria, 41, 758, 1959.

Natta, G., Society of Plastics Engineers (SPE) Journal, 15, 373, 1959.

Natta G., and P. Corradini, Journal of Polymer Science, 20, 251, 1956.

Natta G., and P. Corradini, Journal of Polymer Science, 39, 29, 1959.

Natta G., L. Porri, A. Carbonaro, and G. Luglí, Makromolekular Chemie, 53, 52, 1962.

Noguchi, T., Y. Nakamura, and M. Ichikawa, <u>Journal of Polymer Science: Polymer Letters Edition</u>, <u>11</u>, 15, 1973.

Sadtler Research Laboratories, Carbon-13 NMR, 349C, 1976.

Santee, E.R., Jr., V.D. Mochel, and M. Morton, <u>Journal of Polymer Science: Polymer Letters Edition</u>, <u>11</u>, 449, 1973.

Schilling, F.C., F.A. Bovey, A.E. Tonelli, S. Tseng, and A.E. Woodward, Macromolecules, 17, 728, 1984.

Schilling, F.C., M.A. Gomez, A.E. Tonelli, F.A. Bovey, and A.E. Woodward, Macromolecules, 20, 2957, 1987.

Senn, W.L., Jr., Anal. Chim. Acta, 29, 505, 1963.

Silas, R.S., J. Yates, and V. Thornton, Analytical Chemistry, 31, 529, 1959.

Stellman, J.M., A.E. Woodward, and S.D. Stellman, Macromolecules, 3, 330, 1973.

Suehiro, K., and M. Takayanagi, <u>Journal of Macromolecular Science - Physics</u>, B4(1), 39, 1970.

Tanaka, Y., Y. Takeuchi, M. Kobayashi, and H. Tadokoro, <u>Journal of Polymer Science-Physics</u>, <u>B7</u>, 177, 1973.

Varian Associates, NMR Spectra Catalog, 2, 557, 1963.

White, J.J., A.U. Hasan, and W.C. Sears, <u>Journal of Macromolecular Science-Physics</u>, <u>B7</u>, 177, 1973.

Zerbi, G., and M. Gussoni, Spectrochimica Acta, 22, 2111, 1966.

- Program - Experience of the program of the progra

Zymonas, J., E.R. Santee, Jr., and H.J. Harwood, Macromolecules, 6, 129, 1973.

List of Tables

Table 1: Polymorphism of Trans PBD

IR Data for Syndio PBD Table 2A:

Table 1: Polyworphism of Trans PBD

Table 24: IR Data for Syndio PBD

Table 28: IR Data for Trans PBD

Table 3: In-NMR Data

Table 4: Solid State 13C-NMR Data for Trans PBD

Table 5: DSC Trials

Table 6: Trial Comparisons for Error Determination

Table 7A: Category I, Trials with Varied Cooling and Casting Histories

Table 7B: Category II, Trials with Varied Compositions

TABLE 1: POLYMORPHISM OF TRANS PBD

\$ 500 CONTRACTOR

ACCUPATION OF THE PROPERTY OF

Authors	T(t1) oC	T(tII) oC	H(tI) cal/g	H(tII) cal/g	H(tI)/ H(tII)
Moraglio et al. (1965)	9.2	145	9.04	20.3	2.0
Danusso (1967)	16	145	9.04	20.3	2.0
Natta et al. (1962)	7.5	145	ı	1	ı
Bautz et al. (1981)	7.0	135	ı		ı
Finter and Wegner (1981)	83	164	34.6	16.6	2.1
Bermudez and Fatou (1972)	50-55	142	28.0	16.0	1.8
Dainton et al. (1962)	77	ı	15.1	ı	í
Kijima et al. (1976)	75-78	135-136	31.4	17.1	1.8
Stellman et al. (1973)	73	139	1	í	ı
Berger and Buckley (1963)	60-65	1	i	1	1
Marchetti and Martuscelli (1976)	7.5	139	40.7	20.4	2.0
Mandelkern et al. (1956)	7.4	τ.,	26.5	18.5	1.4
Moller (1987)	67	134	1	ı	1
Iwayanagi et al. (1968)	ı	148	1	ı	l

TABLE 2A: IR DATA FOR SYNDIO PBD (values in cm-1)

this work*	Morero et al.(1960)	other sources**	
662	664	662 M	
667-678		667 B	
		669 Z	
684			
	770		
795	788	787 в	
863	860	855 B	
900-922	908	909 T	
973			
987-1005	991	990 T	
1050	1045	770 1	
1074	1070	1075 B for 1,2 s,i	
1140	1131	1136 B	
1220	1213	1235 E for 1,2 s,i,	9
1220	1265	1233 2 101 1,2 3,1	
1300	1294	1290 B for 1,2 s,i,	•
1315	1310	1307 B for 1,2 s,1	
1336	1333	1325 B for 1,2 s,1,	
1350	1343	1355 B for 1,2 s,1,	
1435	1419	1333 8 101 1,2 8,1,	, а
1457	1452		
1630-1646	1643		
1839	1835		
1912	1910		
1998	1989		
2130	1909		
2280			
2330			
2520			
2570	2550		
2615	2550		
2675	2675		
2830-3000	1		
2630-3000	2847		
	2913		
	2980		
2055-2000	3012		
3055-3080	3080		
3260	~3260		
3360			
3640	1		

^{*} the pen on the IR trace started early, thus these values may be up to 20 cm-1 high in the range of 600-2000 cm-1 and up to 40 cm-1 high in the range of 2000-4000 cm-1

^{**}other sources: B = Binder (1963), M = Morero et al. (1959), S = Silas et al. (1959), T = Tanaka et al. (1971),

Z = Zerbi and Gussoni (1966),

s = syndiotactic, i = isotactic, a = atactic.

TABLE 2B: IR DATA FOR TRANS PBD (values in cm-1)

this work	Morero et	al. (1962) amorphous	othe	r sources**
		764	·	· · · · · · · · · · · · · · · · · · ·
770	773		775	B cryst
908	910*	910*	908	W
938-978	965	965	967	B, H, No
930-970	978	,03	972	B cryst, S
1050	970	1	1050	He cryst
1050				
	105/	1	1053	B cryst
	1054		1054	W
1079		1075	1075	He amorphous
		i	1081	В
1122	1122	ŀ	1120	He cryst
		İ	1230	Не
		,	1232	No
1236	1235	1235	1235	B in all PBD spectra,W
		1	1250	B cryst
1275				•
1308	1312	1312		
1337	1337		1335	He cryst
1350	100.	1351	1350	
1330		1331	1355	B in trans and all 1,2 PBD
1436-1450		1435	1333	b in trans and arr 1,2 rbb
1430-1430	1445	1433	1445	No
	1443	1450	1445	NO
	1/52	1450		
1.625	1453	[
1635				
1665		1		
1685				
1696				
1710		ĺ	~1710	N
1780			~1780	N
1810		ł		
1930	1942	1942		
1980	1984	1984		
2340 broad		İ		
2480	2500	2500		
2520	2535	2535		
2660	2666	2666		
2825-2835	2840	2840		
2860-3020	2895			
2000 3020	2915	2915		
	2950	2313		
	2975	2975		
	47/3			
		3018		

^{*} this band reflects presence of 1,2 units

^{**}other sources: B = Binder (1963),

H = Hampton (1949), He = Hendrix et al. (1971),

N = Natta (1959), No = Noguchi et al. (1973),

S = Silas et al. (1959), W = White et al. (1973).

BLE 3: IH-NWR DATA alues are in ppm)

A STATE OF THE PROPERTY OF THE

Researchers		1,2 PBD >CH2	1,2 PBD assignments >CH2 >CH-	ents •CH2	- HO=	1,4 PBD	1,4 PBD assignments	-HD=	Condicions (temp, solvent, freq)
this work	[\$ 1,2]		2.3	5.1		[c 1,4]	2.2	5.6	150oC, tetralin, 250 MHz
Ashicaka ec al. (1983a)	[s 1,2]	1.33	2.29	4.97	5.58	[1,4]	2.11	5.39	150oC, o-DCB, 200 MHz
Zymonas et al. (1973)	[1,2]	1.2	2.2	8.4	5.5	[1,4]	2.0	5.35	120oC, o-DCB, 100 MHz
Senn (1963)	[1,2]	1.3	;	5.0-5.1	;	[1,4]	2.0	2.0 5.3-5.4	40oC, CC14, 60 MHz
Chen (1962)	;					[1,4]	1.98	5.31	25oC, CC14, 60 MHz
Tanaka et al. (1971)	[a,s 1,2]	1.20	2.10	4.95	2.40	[c 1,4]	2.04	5.42	50oC, CC14, 100 MHz
Hatada et al. (1974)	1					[c 1,4]	2.06	5.45	35oC, CC14, 100 MHz
Santee et al. (1973)	[1,2]	1.3	{	8.4	5.6	[1.99	5.36	110oC, o-DCB, 300 MHz

TABLE 4: SOLID STATE 13C-NMR DATA FOR TRANS PBD (values are in ppm)

1340C	32.8	130.0
122°C	32.8 33.4	130.0
Moller (1987) 52oC 67oC 122oC	33.4	130.0
520C	33.4 35.2	130.0
27 o C	35.2	130.0
187) 650C	34.0	129.5
t al. (19 620C	34.0 35.2	129.5
Schilling et al. (1987) 23oC 59oC 62oC 65oC	34.0 35.2	129.5
230C	35.2	130.7
his work Schilling et al. (1984) 25oC 25oC	333	130 131
This work 25oc	33.2 34.9	129.8

CARLO MACCACON DESCRIPTION DE CONTRACTION DESCRIPTION DESCRIPTION DE CONTRACTION DE CONTRACTI

1 1944 24 100	_	sample	history	heating (oC/min)	trans T(tI)	transition temps (o t]) T(t]] T	oC) T(s)	enthalp H(tI)	enthalpies (cal/g) (tI) H(tII) H(1/g) H(s)	H(t1)/ H(t11)	H(tI)*/ H(tI)**	H(s)*/ H(s)**
### gradia concide mail: -3300/main +10	<u> - ^</u>	syndio	as received	+20						00			
### ### ### ### ### ### ### ### ### ##	. ~	syndio		-			193			. 0			٣.
### 153 1.1.7 1.1.6 1.1.8 1.1.7 1.1.8 1.1.	4	syndio		+20			761			0			4.
### conted 31% C. 250C	2	syndio		-20			155			12			
### \$and beta conted mail3200/min + 20	9	syndto	cast 1550C,							,			
### State	7	syndio	cast 155oC.	07+			3			'n			•
### state ### st				+20			187			•			ň
Frame	∞	syndio	7-7-000	:									
Figure Cooled melt3200/min +10 74 141 20.5 8.0 2.6 0.51 Figure Cooled melt3200/min +10 74 141 20.5 8.0 2.6 0.51 Figure Cooled melt3200/min +20 74 141 21.7 8.7 21.7 8.7 2.5 Figure Cooled melt3200/min +20 74 141 21.7 8.7 21.7 8.7 2.5 Figure Cooled melt200/min +20 74 141 10.6 2.0 0.55 Figure Cooled melt200/min +20 48 141 10.6 2.0 0.40 Figure Cooled melt200/min +20 48 120 -8.1 10.6 0.52 Figure Cooled melt200/min +20 48 120 -8.1 10.6 0.52 Figure Cooled melt200/min +20 2.0 48 120 -8.1 10.6 0.52 Figure Cooled melt3200/min +20 2.5 115 2.7 8.8 2.2 0.45 Figure Cooled melt3200/min +20 2.5 115 2.5 8.8 2.2 0.46 Figure Cooled melt3200/min +10 2.3 2.5 2.5 2.5 0.46 Figure Cooled melt3200/min +10 2.3 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 2.5 Figure Figure Cooled melt3200/min +20 2.5 2.5 2.5 2.5 2.5 2.5 2.5 Figure Figure Figure E.	6	trans	, -32Uo/B1	100	63	150	×		11.7	1.6		ν,	•
trans cooled malt3200/min +10 74 140 20.6 8.0 2.6 0.51 trans cooled malt3200/min +10 74 140 20.6 8.0 2.0 6.53 trans cooled malt3200/min +20 75 140 20.5 8.0 20.5 trans cooled malt200/min +20 80 144 16.0 20.6 8.0 2.0 0.53 trans cooled malt200/min +20 80 144 16.0 10.6 20.6 8.0 0.53 trans cooled malt200/min +20 80 144 16.0 10.6 20.0 0.00 trans crystalized from mult -20 120 120 110 10.6 10.0 0.54 trans crystalized from mult -20 120 110 110 10.6 10.0 0.54 trans crystalized from mult -20 120 110 110 10.6 10.0 0.54 trans crystalized from mult -20 120 110 110 10.6 10.0 0.54 trans crystalized from mult -20 120 110 110 110 10.6 10.0 0.54 trans crystalized from mult -20 120 110 110 110 10.6 10.0 0.54 trans crystalized from mult -20 120 110 110 110 110 110 110 110 110 1	10	trans		+10	7.4	141	_	20.5	8.0		•	.5	
Figure Cooled melt, -200/min +20 141 141 17 7 8 2.8 0.53 158 158 158 0.53 158 158 0.53 158 158 0.53 158 158 0.53 158 158 0.53 158 158 0.53 158 158 0.50 0.50 158 158 0.50 0.50 158 0.50 0.50 158 0.50		trans	melt,	+10	7.4	140		20.6	8		•	٠.	
trans cooled melt, -200/min, +50	7 1	11878	melt,	+20	7.6	141		21.7	8.0			٠,٠	
trans cooled mell200/min, +20	1 4	11411	melt,	05+	80	144		16.1				. 4	
trans cooled at 900 for 10min	15	trans			}	•) •		•		
trans cooled maelt, -200 min, +20 trans crystallized from melt -20 trans cooled melt, -3200/min +20 50/50 cast 1600c, cooled melt, -3200/min +10 50/50 cast 1600c, cooled melt, -200/min +10 50/50 ca				+20		141					_	.52	
trans crystallized from melt -20 48 120 11.0 0.54 trans crystallized from melt -20 48 120 11.0 0.54 trans crystallized from melt -20 120 11.0 0.64 trans crystallized from melt -20 25 115 0.40 trans cast 160cc, cast 160cc, cooled 3hr to 25cc 120 min +20 77 131 19.5 8.8 cooled melt, -320c/min +20 77 131 19.5 8.8 cooled melt, -320c/min +20 77 131 19.5 8.8 50/50 cast 160cc, cooled melt, -320c/min +20 72 129 194 7.9 3.8 6.7 2.1 0.39 50/50 cast 160cc, cooled melt, -320c/min +20 70 123 185 6.7 2.7 4.9 2.5 0.33 50/50 cast 160cc, cooled melt, -320c/min +20 70 123 184 6.4 2.6 4.7 2.5 0.33 50/50 cast 160cc, cooled melt, -320c/min +20 70 123 184 6.4 2.6 4.7 2.5 0.33 50/50 cast 160cc, cooled melt, -320c/min +20 70 123 184 6.4 2.6 4.7 2.5 0.35 50/50 cast 160cc, cooled melt, -20c/min +20 64 103 164 3.5 1.2 3.6 2.9 0.17 50/50 cast 160cc, cooled melt, -20c/min +20 70 123 180 5.3 2.1 5.5 2.6 0.25 50/50 cast 160cc, cooled melt, -20c/min +20 70 123 180 5.3 2.1 5.5 2.6 0.25 50/50 cast 160cc, cooled melt, -20c/min +20 70 123 180 5.3 2.1 5.5 2.0 0.25 50/50 cast 160cc, cooled 3hr to 25cc 10min +20 70 70 180 181 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 112/8/87 +20 70 123 180 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 112/8/87 +20 70 123 180 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 112/8/87 +20 70 123 180 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 112/8/87 +20 70 123 180 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 0111/2/87 +20 70 120 181 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 181 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 181 181 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 181 181 5.3 2.7 5.5 5.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 181 181 5.3 2.7 5.5 5.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 180 5.3 2.7 5.5 2.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 180 5.3 2.7 5.5 5.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 180 5.3 2.7 5.5 5.0 0.25 50/50 cast 100cc 0112/8/87 +20 70 120 180 5.3 2.7 5.5 5.0 0.25 50/50 cast 100cc 0112/8/87 +20 70		trans	cooled melt, -200/min,										_
trans crystallized from melt -20 48 120 -17.6 -7.8 0.43			or 2(+20		141						. 54	
trans crystallized from melt -20 1120 -8.1 0.440 trans crystallized from melt -20 1150 -8.1 trans cooled melt -20 77 131 19.5 8.8 2.2 0.48 trans cooled melt -3200/min +20 74 126 18.5 7.7 trans cast 160c, -3200/min +10 73 125 180 8.1 2.2 0.44 50/50 cast 160c, -3200/min +10 73 125 184 6.4 2.6 4.7 2.5 0.33 50/50 cast 160c, -3200/min +20 70 123 184 6.4 2.6 4.7 2.5 0.33 50/50 cast 160c, -3200/min +20 70 123 184 6.4 2.6 4.7 2.5 0.32 50/50 cast 160c, -3200/min +20 70 123 184 6.4 2.6 4.7 2.5 0.32 50/50 cast 160c, -3200/min +20 70 123 184 6.4 2.6 4.7 2.5 0.32 50/50 cast 160c, -3200/min +20 64 103 164 3.5 1.2 3.6 2.9 0.17 50/50 cast 160c, -3200/min +20 4.7 4.1 4.0 4.7 2.5 50/50 cast 160c, -3200/min +20 4.7 4.1 4.0 4.1 50/50 cast 160c, -3200/min +20 4.7 4.1 4.0 4.1 50/50 cast 160c, -3200/min +20 4.7 4.1 50/50 cast 160c, -3200/min +30 4.1 60/50 60/50 60/50 4.1 60/50 60/50 60/50 4.1 60/50 60/50	17	trans	from	-20		120		-17.6			•	.43	
trans crystallized from melt -50 25 115 -7.6	200	rrans	from f	-20		120				•	-	 	•
trans cast 1600c, to 250c	200	0 0 0 0 1	1 4	071	٠ ۲	115			۰,	-		, ,	
trans cast 1600C, cooled 3hr to 250C	2 2 2	trans	1	2) •				•			•	
trans cast 1600C, cast 1200C on 12/8/87 cast 1200C on			cooled 3hr to 25oC	+20	7.7	131		•	•			4.	
trans cooled welt, -3200/min +20	22	trans				,					,	•	
Cooled melt, -320o/min +10 73 125 18.0 8.1 2.2 0.44 50/50 cast 1600C, cooled melt, -320o/min +10 72 129 194 7.9 3.8 6.7 2.1 0.39 50/50 cast 1600C, cooled melt, -320o/min +10 70 123 184 6.4 2.6 4.7 2.5 0.32 50/50 cast 1600C, cooled melt, -320o/min +20 64 103 164 3.5 1.2 3.6 2.9 0.17 50/50 cast 1600C, cooled melt, -20o/min +20 64 103 164 3.5 1.2 3.6 2.9 0.17 50/50 cast 1600C, cooled melt, -20o/min +20 70 123 184 6.4 2.6 4.7 2.5 0.32 50/50 cast 1600C, cooled melt, -20o/min +20 70 107 164 7.5 2.5 0.07 50/50 cast 1600C, cooled melt, -20o/min +20 73 102 180 5.3 2.1 5.5 2.6 0.26 50/50 cast 1200C on 11/22/87 +20 74 108 181 5.3 2.7 5.5 2.0 0.26	,	1 1		+20	7.4	126		•	7.7		7.4	4	
50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 160oC, 50/50 cast 120oC on 12/8/87 50/50 cast 120oC 50/50 cast 120oC on 12/8/87 420 73 50/50 cast 120oC on 11/22/87 420 74 50/50 cast 120oC on 11/22/87 420 5.3 50/50 cast 120oC on 11/22/87 420 74 420 5.3 5.3 2.7 5.3 2.7 5.3 2.7 <td>7</td> <td>8118</td> <td></td> <td>+10</td> <td></td> <td>125</td> <td></td> <td>18.0</td> <td>~</td> <td></td> <td>2.2</td> <td>0.44</td> <td></td>	7	8118		+10		125		18.0	~		2.2	0.44	
SO/50 cooled 3hr to 25oC +20 72 129 194 7.9 3.8 6.7 2.1 0.39 SO/50 cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 160oC, cast 120oC on 12/8/87 107 164 3.5 1.2 3.6 4.7 2.5 0.32 SO/50 cast 160oC, cast 120oC on 12/8/87 +20 64 103 164 3.5 1.2 3.6 2.9 0.17 SO/50 cast 160oC, cast 120oC on 11/22/87 +20 107 164 3.5 1.2 4.1 0.07 SO/50 cast 120oC on 11/22/87 +20 73 102 180 5.3 2.1 5.5 2.6 0.26 SO/50 cast 120oC on 11/22/87 +20 74 108 181 5.3 2.7 5.5 2.6 0.26	24	50/50											
50/50 cast 1600C, cooled melt, -3200/min +20 70 123 185 6.7 2.7 4.9 2.5 0.33 50/50 cast 1600C, cooled melt, -3200/min +10 70 123 184 6.4 2.6 4.7 2.5 0.32 50/50 cast 1600C, cooled melt, -200/min +20 64 103 164 3.5 1.2 3.6 2.9 0.17 50/50 cast 1600C, cooled melt -200/min +20 107 164 0.7 4.1 0.07 50/50 cast 1600C, cooled 3nr to 25oC 1200C on 112/8/87 +20 73 102 180 5.3 2.7 5.5 2.6 0.26 50/50 cast 1200C on 112/8/87 +20 74 108 181 5.3 2.7 5.5 2.0 0.26	7	03/03	t o	+20	72		6	7.9	3.8	6.7	2.1	۳.	0.54
50/50 cast 1600c, 50/50 cast 1600c, 50/50 cast 1600c, 50/50 cast 1600c, 50/50 cast 1600c, cooled melt, -200/min held at 900 for 10min 50/50 cast 1600c, cooled melt, -200/min held at 900 for 10min 50/50 cast 1600c, cooled melt, -200/min held at 900 for 10min 50/50 cast 1200c on 11/28/87 cooled 3hr to 250c 50/50 cast 1200c on 11/22/87 4-20 73 102 180 5.3 2.1 5.5 2.6 0.26 50/50 cast 1200c on 11/22/87 50/50 cast 1200c on 11/22/87 4-20 73 102 180 5.3 2.1 5.5 2.0 0.26	7	00/00		+20	7.0	123	00	6.7	2.7	•	2.5	٠,	٣,
50/50 cast 1600C, cooled melt, -200/min +10 /0 123 184 6.4 2.6 4./ 2.5 0.32 50/50 cast 1600C, cooled melt, -200/min +20 64 103 164 3.5 1.2 3.6 2.9 0.17 50/50 cast 1600C, cooled melt, -200/min +20 107 164 0.7 4.1 0.07 50/50 cast 1200C on 12/8/87 +20 73 102 180 5.3 2.1 5.5 2.6 0.26 50/50 cast 1200C on 11/22/87 +20 74 108 181 5.3 2.7 5.5 2.0 0.26	56	20/20			;				,		•	,	•
50/50 cast 1600C, cooled melt, -200/min +20 64 103 164 3.5 1.2 3.6 2.9 0.17 50/50 cast 1600C, cooled melt, -200/min +20 107 164 0.7 4.1 0.07 50/50 cast 1600C, cooled from melt -20 73 102 180 5.3 2.1 5.5 2.6 0.26 50/50 cast 1200C on 11/22/87 +20 73 102 180 5.3 2.7 5.5 2.0 0.26	27	50/50		+10	0 /		œ	7.9	5.6		2.5	0.32	,
50/50 cast 1600C, cooled melt, -200/min held at 900 for 10min 50/50 cast 1600C, cost at 1200C on 12/8/87 cooled 3hr to 25oC 50/50 cast 1200C on 11/22/87	;))		+20	79	03	9	3.5	•	•	•	7.	
SO/50 cast 1600C, cast 1200C on 11/22/87 -20 73 102 181 5.3 2.7 4.1 0.07° 50/50 cast 1200C on 11/22/87 +20 73 102 180 5.3 2.1 5.5 2.6 0.26 50/50 cast 1200C on 11/22/87 +20 74 108 181 5.3 2.7 5.5 2.0 0.26	28	50/50											
50/50 cast 1600C, crystallized from melt -20 50/50 cast 1200C on 12/8/87 cooled 3hr to 25oC 50/50 cast 1200C on 11/22/87 50/50 cast 1200C on 11/22/87			_ "	0	<u> </u>		771					0 0	33
50/50 cast 120oC on 12/8/87 +20 73 102 180 5.3 2.1 5.5 2.6 0.26 50/50 cast 120oC on 11/22/87 +20 74 108 181 5.3 2.7 5.5 2.0 0.26	29	50/50	cast 160oC.	07+			*		•	;		2	
50/50 cast 120oC on 12/8/87	<u> </u>		crystallized from melt	-20			126			0.4-			0.33
50/50 cast 120oC on 11/22/87	30	20/20	cast 120oC on 12/8/87		÷		-		•				
cooled 3hr to 250C +20 74 108 181 5.3 2.7 5.5 2.0 0.26 0	7	50/50	ם ם	07+	۲,		0.81	٠.٢	7 - 7	•	9.7	07.0	***
	;)	t :	+20	7.4		181	5.3	2.7	•	2.0	0.26	0.44

የመመመመው መመመመ ያለው የመመመ ው መመመመው ያለው አንድር እና አንድር እና አንድር እና አ

* enthalpy per gram of component, not total sample **theoretical enthalpy of 1003 crystallized sample ^ value based on H(tII) enthalpies

TABLE 6: TRIAL COMPARISONS FOR ERROR DETERMINATION

100200000

CONTRACT OF THE PROPERTY OF TH

sample	history	heating (oC/min)	transition T(tI)	heating transition temps (oC) (oC/min) T(tI) T(tII)	<pre>enthalpy (cal/g) H(tI) H(tII)</pre>	(cal/g) H(tII)	**
trans	cooled melt, -3200/min	+10	74	141	20.5	8.0	10
trans	cooled melt, -320o/min	+20	76	141	21.7	7.8	12
trans	crystallized from melt	-20	8	120	-17.6	-7 -8 -1 -8 -1	17

	a a m p i c	history	(oC/min)	transi T(tI)	tion temps T(tII)	(0C) T(s)	enthal H(tI)	pies (cal H(tII)	/g) H(s)	H(tl)*/ H(tl)**	H(s)*/ H(s)**	*
٧ı	Bys	0 m	+10			193			19.3		0.79	3 6
		cast 155oC, cooled melt, -320o/min	+10			183			9.1		0.37	∞
	nys	eceive ed sel	+20			193			19.1		0.78	14
		cast 1550C, cooled 3hr to 25oC	+20			197			15.9		9.65	•
		cast 1550C, cooled melt, -320o/min	+20			187			9.6		0.39	
	1 8 1 8 1 8 1 8 1 8 1 8 1 8 1 8 1 8 1 8	cooled melt, -3200/min cooled melt, -3200/min	001++	63 74 74	150 141 140		20.5	11.7 8.0 8.0		0.58 0.51 0.51		9 10 11
		- P	+10	73	125		18.0	8.1		77.0		23
	trans	-3200/m1 -3200/m1	+20	7 6 7 7	141 140		21.7	7.8		0.53		12
		mett, -200/min t 900 for 10min melt -200/min	+20		141			10.6		0.52		1.5
		at 900 for 20 1600C.	+20		141			11.0		0.54~		16
	-	led 3hr	+20	7.7	131		19.5	8.8	•	0.48		2 1
		, .D	+20	74	126		18.5	7.7		0.46		22
	50/50	cast 160oC, cooled melt, -320o/min	+20	7.0	123	185	6.7	2.7	6.4	0.33	0.39	25
		ed 3hr to	+20	7.2	129	194	7.9	3.8	6.7	0.39	0.54	24
		12000 on 12/0/0 ed 3hr to 250C 1200C on 11/22/	+20	7.3	102	180	5.3	2.1	5.5	0.26	0.44	30
		ed 3hr to 25oC	+20	74	108	131	5.3	2.7	5.5	0.26	0.44	31

heating (oC/min)	. C	transition temps T(tI) T(tII)	remps (oC) I) T(s)	enthal H(tI)	H(tI) H(tII) H(H(s)	H(tI)*/ H(tI)**	H(s)*/
+2	0.0	72 129	194	7.9	3.8	6.7	0.39	0.54
	+20		197		1	15.9		0.65
•	+20	77 131		19.5	8.8		0.48	
•	+20	70 123	185	6.7	2.7	6.4	0.33	0.39
	+20		187			9.6		0.39
	+20	74 126		18.5	7.7		97.0	
	+10	70 123	184	6.4	2.6	4.7	0.32	0.38
	+10		183			9.1		0.37
	+10	73 125		18.0	8.1		77.0	

List of Figures

Personal Property and Personal Property

District of the Control of Special Control of the C


Figure 1: IR Spectra for Syndio PBD

Figure 2: IR Spectra for Trans PBD

Figure 3: 1H-NMR Spectra


Figure 4: Solid State MAS 13C-NMR Spectra

Figure 1: IR Spectra for Syndio PBD




la. Morero et al. (1960)

TENANDOCT TO THE PROPERTY




lb. Goodyear sample


Figure 2: IR Spectra for Trans PBD



2a. Morero et al. (1962)



2b. Goodyear sample .



2c. cast Goodyear sample


Figure 3: ¹H-NMR Spectra

+							
1888 - ⊤ 1 +++ + 1 + - 1 + 1 + 1						- benins	
				45 13 14 14 14			
							· -· ·
9							· · · · · ·
				وما مستوهدية والطاء والأ			
L							
((
	<u> </u>						
		,		,			
				::::t:=:::::::			
							· · - · ·
1 les							
	ļ						
<u> </u>							
- han,					1 1.4		
	II				·· ·		
	de 						
	H						
	 				~ : ~ : ~ //. : _ :		
							1
I Take Time Take (-/
	1						
40	7.0	3.6	40	70		1.0	
	-	-			_		


はのおかかから 全体をなる

Proposed Pro


3a. Tetralin




3b. Syndio PBD



3c. Trans PBD



4a. Syndio PBD



4b. Trans PBD

r + 1 '

Control of the second s

DL/1113/87/2

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	No. Copies		No. Copies
Office of Naval Research Attn: Code 1113 800 N. Quincy Street Arlington, Virginia 22217-5000	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 50C Crane, Indiana 47522-5050	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	1
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko, Code L52 Port Hueneme, California 93401	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12 high quality	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
DTNSRDC Attn: Dr. H. Singerman Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 1911	1
Dr. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375-5000	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1

E N D DATE FILMED 8-88 DTIC